


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		released for production.	5/25/2016	DPD	JAG
2	17-0171	C20-300K ADDED DIM 2X R.19.	7/13/2017	DPD	JAG







NOTE:

DWG NO.

1. NICKEL PLATE .0004 - .0006, BAKE AFTER PLATING.

KEEPERLESS LOAD BEAM ASSEMBLY

C20-300KA UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ± .5°
.X ± .1 SURFACES = 125/ TREAT FINISH SEE NOTE 1 SURFACES = 125 SPEC

A T.I.

1. BREAK ALL SHARP EDGES

.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 DRAWN BY: WALLRICH CHECKED: CLOUGH UNIT QTY ASSY QTY ASSY QTY OPPS APPR: **B/O INFORMATION OR SPECIFICATIONS** PG. ANDERSON B/O Part # Description Material QA APPR: USED ON MODEL LINDSAY C20-300K LOAD BEAM 4140/4142 2 APPROVED: GILBERT SCALE 6/5/2015 SHEET 1 OF 2 C20-311 1:4 TRUNNION

